



Bearing No. 62/28ZZ

D	58 mm
d	28 mm
B	16 mm
C	16 mm
rn	0,5 mm
Noun	Bearing
Bore	1.102 Inch 28 Millimeter
UNSPSC	31171504
da max	35,5 mm
Weight	0,171 Kg
r min.	1 mm
da min.	33 mm
Da max.	53 mm
ra max.	1 mm
series:	62
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	28x58x16
Inventory	0.0
Snap Ring	No
Width (mm)	16
bore type:	Round
Weight / LBS	0.366
maximum rpm:	12000 RPM
closure type:	Double Shielded
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove
Bearing number	62/28ZZ
overall width:	16 mm
bore diameter:	28 mm
cage material:	Steel
fillet radius:	1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outer Race Width	0.63 Inch 16 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.283 Inch 58 Millimeter
Long Description	28MM Bore; 58MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.ntnamerica.com
bearing material:	High Carbon Chrome Steel
outside diameter:	58 mm
inner ring width:	16 mm
Manufacturer Name	NTN
Weight / Kilogram	0.166
outer ring width:	16 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	28
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring

Outer Diameter (mm)	58
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	9750 N
maximum rpm (grease):	12000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	17900 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	62/28ZZ
Internal Special Features	No
manufacturer product page:	Click here
(Grease) Lubrication Speed	12 000 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	17,9 kN
Basic static load rating (C0)	9,75 kN
Maximum Capacity / Filling Slot	No