



### Bearing No. 6203-2Z/VA201

D	40 mm
d	17 mm
B	12 mm
C	12 mm
d1	24,5 mm
D2	35 mm
Bore	0.669 Inch   17 Millimeter
Noun	Bearing
Weight	0,065 Kg
UNSPSC	31171504
r1 min.	0,6 mm
r2 min.	0,6 mm
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Inventory	0.0
Snap Ring	No
Size (mm)	17x40x12
Width (mm)	12
Weight / LBS	0.146
Mass bearing	0.068 kg
Temperature -	30 to +250 °
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Keyword String	Ball
Limiting speed	150 r/min
Other Features	Deep Groove   Extreme Temperature Variant
Bearing number	6203-2Z/VA201
Rolling Element	Ball Bearing

Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	1.575 Inch   40 Millimeter
Outer Race Width	0.472 Inch   12 Millimeter
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Fea
Manufacturer Name	SKF
Weight / Kilogram	0.066
D <sub>a</sub> max.	35.8 mm
Bore Diameter (mm)	17
Internal Clearance	C0-Medium
r <sub>a</sub> max.	0.6 mm
d <sub>a</sub> min.	21.2 mm
d <sub>a</sub> max.	24.4 mm
Outer Diameter (mm)	40
Minimum Buy Quantity	N/A
r <sub>1,2</sub> min.	0.6 mm
D <sub>2</sub> ?	34.98 mm
d <sub>1</sub> ?	24.5 mm
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	Polyalkylene Glycol/Graphite Mixture Filled
Basic dynamic load rating C	9.95 kN

Limiting temperature T max.	250 °C
Basic static load rating (C <sub>0</sub> )	4,75 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C <sub>0</sub>	4.75 kN