



Bearing No. 74537/74850

|                                 |                      |
|---------------------------------|----------------------|
| R                               | 3,6 mm               |
| a                               | 2,3 mm               |
| d                               | 136,525 mm           |
| D                               | 215,9 mm             |
| T                               | 47,625 mm            |
| B                               | 47,625 mm            |
| C                               | 34,925 mm            |
| r                               | 3,3 mm               |
| Ab                              | 2 mm                 |
| Aa                              | 4,8 mm               |
| Db                              | 196 mm               |
| da                              | 148 mm               |
| db                              | 155 mm               |
| Da                              | 208 mm               |
| Weight                          | 6,27 Kg              |
| Size (mm)                       | 136.525x215.9x47.625 |
| Width (mm)                      | 47,625               |
| Factor (K)                      | 1,2                  |
| Factor (G1)                     | 362,9                |
| Factor (Cg)                     | 0,0383               |
| Factor (G2)                     | 68,5                 |
| Bearing number                  | 74537/74850          |
| Bore Diameter (mm)              | 136,525              |
| Outer Diameter (mm)             | 215,9                |
| Calculation factor (e)          | 0,49                 |
| Basic static load rating (C0)   | 614 kN               |
| Basic dynamic load rating (C1)  | 354 kN               |
| Basic dynamic load rating (C90) | 91,7                 |

|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 76,5 |
|----------------------------------|------|