



Bearing No. 359S/354A

e	0.31
d	46,038 mm
D	85 mm
T	20,638 mm
B	21,692 mm
C	17,462 mm
a	15,4 mm
Da	77 mm
B_	21.692
Db	80 mm
da	55 mm
Y0	1.1
db	51 mm
C0	81.5
D_	85
Z_	16
C_	17.462
Y1	2
DE_	75.506
SLR	14.7
D_a	77
DI_	54.641
DA1	10.776
DA2	9.967
CUP	0.162
DA_	10.374
D_b	80
RAr	195
SDM_	64.901
KBRG	3161

yobi	359S/354A
CONE	0.343
ALP21	23
ALP22	5
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	10
r min.	2,3 mm
LangID	1
Weight	0,505 Kg
ALPHA_	11.542
r1 min.	1,3 mm
ra max.	2,3 mm
Oil rpm	6000
outer r	1.3
hidYobi	359S/354A
GRS rpm	4300
inner r	2.3
hidTable	ecat_NSTPRI
inner ra	2.3
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	46.038x85x20.638
SHOG_yobi	359SR/354AR
Prod_Type3	TRBSR_ID_A
Width (mm)	20,638
Bearing number	359S/354A
Bore Diameter (mm)	46,038
Outer Diameter (mm)	85
Calculation factor (e)	0,31

(Oil) Lubrication Speed	6000 r/min
Calculation factor (Y0)	1,1
(Grease) Lubrication Speed	4300 r/min
Basic static load rating (C0)	81,5 kN
Basic dynamic load rating (C)	71,5 kN