



### Bearing No. 6203LLU

C	12 mm
d	17 mm
D	40 mm
B	12 mm
Bore	0.669 Inch   17 Millimeter
Noun	Bearing
Weight	0,066 Kg
da max	23 mm
UNSPSC	31171504
r min.	0,6 mm
da min.	21 mm
ra max.	0,6 mm
series:	62
Da max.	36 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	17x40x12
Inventory	0.0
Snap Ring	No
Width (mm)	12
bore type:	Round
maximum rpm:	21000 RPM
Weight / LBS	0.141
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	17 mm
Keyword String	Ball

overall width:	12 mm
cage material:	Steel
fillet radius:	0.6 mm
Bearing number	6203LLU
Enclosure Type	Contact Seal
Reference speed	12 000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outer Race Width	0.472 Inch   12 Millimeter
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	1.575 Inch   40 Millimeter
outside diameter:	40 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.064
inner ring width:	12 mm
outer ring width:	12 mm
Manufacturer Name	NTN
Bore Diameter (mm)	17
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	40

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	12000 rpm
static load capacity:	4600 N
dynamic load capacity:	9600 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6203LLU
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	4,6 kN
Basic dynamic load rating (C)	9,6 kN
Maximum Capacity / Filling Slot	No