



Bearing No. 6203VV

D	40 mm
d	17 mm
B	12 mm
C	12 mm
r	0.6
Z_	8
B_	12
D_	40
ra	0.6
C0	4.8
fo	13.2
DI_	22.253
SRI	3.41
D_a	36
DE_	35.747
DA_	6.747
SRE	3.58
SRIN	0
SBRG	2
yobi	6203VV
SDM_	29
SREX	0.04
KBRG	6151
bomp	0
mass	0.067
Bore	0.669 Inch 17 Millimeter
SRIX	0.02
SREN	0
Noun	Bearing

ALPHA_	0
da min	21
LangID	1
r min.	0,6 mm
UNSPSC	31171504
da max	23,5 mm
C_conv	9550
Weight	0,067 Kg
ra max.	0,6 mm
hidYobi	6203VV
GRS rpm	17000
da min.	21 mm
Da max.	36 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	17x40x12
Enclosure	2 Seals
Inventory	0.0
Width (mm)	12
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.065
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6203VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.472 Inch 12 Millimeter
Outside Diameter	1.575 Inch 40

	Millimeter
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.03
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	17
Outer Diameter (mm)	40
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6203VV
Internal Special Features	No
(Grease) Lubrication Speed	17 000 r/min
Basic static load rating (C0)	4,8 kN
Basic dynamic load rating (C)	9,55 kN
Maximum Capacity / Filling Slot	No