



Bearing No. 6203ZENR

b	1.35 mm
f	1.12 mm
d	17 mm
D	40 mm
B	12 mm
C	12 mm
a	2.06 mm
D2	44.6 mm
D1	38.1 mm
r1	0.5 mm
Noun	Bearing
Bore	0.669 Inch 17 Millimeter
Width	12 mm
r min.	0.6 mm
Weight	0.065 Kg
UNSPSC	31171504
b (min)	1.4 mm
r1 min.	0.5 mm
a (max)	2.1 mm
D1 (max)	38.1 mm
Cy (max)	2.9 mm
Category	Single Row Ball Bearing
Da (max)	35 mm
Dx (min)	45.5 mm
ra (max)	0.6 mm
da (min)	22 mm
Inventory	0.0
Factor fo	13.1
Enclosure	1 Metal Shield

Bore Size	17 mm
Snap Ring	Yes
Bore Type	Cylindrical Bore
Size (mm)	17x40x12
Width (mm)	12
Weight / LBS	0.146
Configuration	Single Row
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Other Features	Deep Groove With Snap Ring
Bearing number	6203ZENR
Keyword String	Ball
Snap Ring Width	1.1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Radial Clearance	0.003 to 0.018 mm
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Outer Race Width; 1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.nachiamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.472 Inch 12 Millimeter
Outside Diameter	1.575 Inch 40 Millimeter
Weight / Kilogram	0

Manufacturer Name	NACHI
Bore Diameter (mm)	17
Internal Clearance	C0-Medium
Static Load Rating	4,800 N
Outer Diameter (mm)	40
Dynamic Load Rating	9,550 N
Minimum Buy Quantity	N/A
Limiting Speed - Oil	21,000 rpm
Fillet Radius/Chamfer	0.6 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	18,000 rpm
Internal Special Features	No
(Grease) Lubrication Speed	17000 r/min
Snap Ring Outside Diameter	44.6 mm
Basic static load rating (C0)	4,8 kN
Basic dynamic load rating (C)	9,55 kN
Maximum Capacity / Filling Slot	No