



Bearing No. 71940 ACD/HCP4AH1

K	0.6 mm
a	75.2 mm
d	200 mm
D	280 mm
B	38 mm
Ball - z	26
Size (mm)	280x200x38
Width (mm)	38
Mass bearing	5.11 kg
d <sub>n</sub>	231.4 mm
D <sub>1</sub>	255.3 mm
d <sub>1</sub>	224.7 mm
C <sub>1</sub>	10 mm
D <sub>1</sub>	255.3 mm
d <sub>2</sub>	224.7 mm
C <sub>1</sub>	10 mm
d <sub>1</sub>	224.7 mm
d <sub>n</sub>	231.4 mm
d <sub>2</sub>	224.7 mm
Bearing number	71940 ACD/HCP4AH1
Preload class B	704 N/micron
Preload class A	538 N/micron
Preload class D	1274 N/micron
G <sub>ref</sub>	81 cm <sup>3</sup>
Preload class C	938 N/micron
Number of balls z	26
Bore Diameter (mm)	280
r <sub>b</sub> max.	1 mm
r <sub>a</sub> max.	2 mm

D <sub>b</sub> max.	275 mm
D <sub>a</sub> max.	271 mm
d <sub>a</sub> min.	209 mm
d <sub>b</sub> min.	209 mm
Outer Diameter (mm)	200
r <sub>a</sub> - max.	2 mm
D <sub>a</sub> - max.	271 mm
d <sub>b</sub> - min.	209 mm
d <sub>a</sub> - min.	209 mm
r <sub>1,2</sub> min.	2.1 mm
r <sub>3,4</sub> min.	1 mm
Ball - D <sub>w</sub>	25.4 mm
r <sub>b</sub> - max.	1 mm
D <sub>b</sub> - max.	275 mm
Calculation factor f	1.23
Calculation factor e	0.68
Calculation factor - f	1.23
r <sub>1,2</sub> - min.	2.1 mm
r <sub>3,4</sub> - min.	1 mm
Calculation factor - e	0.68
Ball diameter D <sub>w</sub>	25.4 mm
Basic dynamic load rating C	199 kN
Preload class A G <sub>A</sub>	1250 N
Preload class B G <sub>B</sub>	2500 N
Preload class C G <sub>C</sub>	5000 N
Basic dynamic load rating - C	199 kN
Preload class D G <sub>D</sub>	10000 N
Preload class B - G <sub>B</sub>	2500 N
Preload class A - G <sub>A</sub>	1250 N
Preload class D - G <sub>D</sub>	10000 N

Preload class C - $G_C$	5000 N
Fatigue load limit $P_u$	6.8 kN
Calculation factor $f_1$	0.98
Calculation factor $f_{2A}$	1
Calculation factor $f_{2B}$	1.07
Calculation factor $f_{2C}$	1.12
Calculation factor $f_{2D}$	1.17
Calculation factor $f_{HC}$	1.04
Calculation factor - $Y_1$	0.92
Calculation factor - $Y_2$	1.41
Calculation factor - $Y_0$	0.76
Calculation factor - $X_2$	0.67
Calculation factor - $f_1$	0.98
Limiting speed for oil lubrication	7500 mm/min
Fatigue load limit - $P_u$	6.8 kN
Calculation factor - $f_{2D}$	1.17
Calculation factor - $f_{HC}$	1.04
Calculation factor - $f_{2C}$	1.12
Calculation factor - $f_{2B}$	1.07
Calculation factor - $f_{2A}$	1
Limiting speed for grease lubrication	5000 r/min
Basic static load rating $C_0$	250 kN
Static axial stiffness, preload class A	538 N/ $\mu$ m
Static axial stiffness, preload class D	1274 N/ $\mu$ m
Static axial stiffness, preload class C	938 N/ $\mu$ m
Static axial stiffness,	704 N/ $\mu$ m

preload class B	
Attainable speed for grease lubrication	5000 r/min
Basic static load rating - $C_0$	250 kN
Attainable speed for oil-air lubrication	7500 r/min
Reference grease quantity $G_{ref}$	81 cm <sup>3</sup>
Calculation factor (single, tandem) $Y_2$	0.87
Calculation factor (single, tandem) $Y_0$	0.38
Calculation factor (single, tandem) $X_2$	0.41
Calculation factor (back-to-back, face-to-face) $Y_1$	0.92
Calculation factor (back-to-back, face-to-face) $Y_2$	1.41
Calculation factor (back-to-back, face-to-face) $Y_0$	0.76
Calculation factor (back-to-back, face-to-face) $X_2$	0.67