



Bearing No. 71940 ACD/P4AH1

K	0.6 mm
a	75.2 mm
d	200 mm
D	280 mm
B	38 mm
Ball - z	26
Size (mm)	280x200x38
Width (mm)	38
Mass bearing	6.1 kg
d _n	231.4 mm
D ₁	255.3 mm
d ₁	224.7 mm
C ₁	10 mm
D ₁	255.3 mm
d ₂	224.7 mm
C ₁	10 mm
d ₁	224.7 mm
d _n	231.4 mm
d ₂	224.7 mm
Bearing number	71940 ACD/P4AH1
Preload class B	635 N/micron
Preload class A	484 N/micron
Preload class D	1148 N/micron
G _{ref}	81 cm ³
Preload class C	845 N/micron
Number of balls z	26
Bore Diameter (mm)	280
r _b max.	1 mm
r _a max.	2 mm

D _b max.	275 mm
D _a max.	271 mm
d _a min.	209 mm
d _b min.	209 mm
Outer Diameter (mm)	200
r _a - max.	2 mm
D _a - max.	271 mm
d _b - min.	209 mm
d _a - min.	209 mm
r _{1,2} min.	2.1 mm
r _{3,4} min.	1 mm
Ball - D _w	25.4 mm
r _b - max.	1 mm
D _b - max.	275 mm
Calculation factor f	1.23
Calculation factor e	0.68
Calculation factor - f	1.23
r _{1,2} - min.	2.1 mm
r _{3,4} - min.	1 mm
Calculation factor - e	0.68
Ball diameter D _w	25.4 mm
Basic dynamic load rating C	199 kN
Preload class A G _A	1250 N
Preload class B G _B	2500 N
Preload class C G _C	5000 N
Basic dynamic load rating - C	199 kN
Preload class D G _D	10000 N
Preload class B - G _B	2500 N
Preload class A - G _A	1250 N
Preload class D - G _D	10000 N

Preload class C - G_C	5000 N
Fatigue load limit P_u	6.8 kN
Calculation factor f_1	0.98
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.04
Calculation factor f_{2C}	1.08
Calculation factor f_{2D}	1.14
Calculation factor f_{HC}	1
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Calculation factor - f_1	0.98
Limiting speed for oil lubrication	6300 mm/min
Fatigue load limit - P_u	6.8 kN
Calculation factor - f_{2D}	1.14
Calculation factor - f_{HC}	1
Calculation factor - f_{2C}	1.08
Calculation factor - f_{2B}	1.04
Calculation factor - f_{2A}	1
Limiting speed for grease lubrication	4300 r/min
Basic static load rating C_0	250 kN
Static axial stiffness, preload class A	484 N/ μ m
Static axial stiffness, preload class D	1148 N/ μ m
Static axial stiffness, preload class C	845 N/ μ m
Static axial stiffness,	635 N/ μ m

preload class B	
Attainable speed for grease lubrication	4300 r/min
Basic static load rating - C_0	250 kN
Attainable speed for oil-air lubrication	6300 r/min
Reference grease quantity G_{ref}	81 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67