



Bearing No. 72200/72487

| | |
|------|------------|
| e | 0.74 |
| d | 50,8 mm |
| D | 123,825 mm |
| T | 36,512 mm |
| B | 32,791 mm |
| C | 25,4 mm |
| a | 37 mm |
| Da | 102 mm |
| B_ | 32.791 |
| Db | 116 mm |
| da | 74 mm |
| Y0 | 0.45 |
| db | 66 mm |
| C0 | 160 |
| D_ | 123.825 |
| Z_ | 14 |
| C_ | 25.4 |
| Y1 | 0.81 |
| DE_ | 100.865 |
| SLR | 23 |
| D_a | 102 |
| DI_ | 69.761 |
| DA1 | 18.23 |
| DA2 | 14.932 |
| CUP | 0.79 |
| DA_ | 16.608 |
| D_b | 116 |
| RAr | 125.485 |
| SDM_ | 85.399 |
| KBRG | 3161 |
| | |

| | |
|------------------------|---------------------|
| yobi | 72200/72487 |
| CONE | 1.22 |
| ALP21 | 52 |
| ALP22 | 20 |
| ALP23 | 0 |
| BETA_ | 4 |
| BET21 | 8 |
| BET23 | 0 |
| BET22 | 20 |
| r min. | 3,5 mm |
| LangID | 1 |
| Weight | 2,01 Kg |
| ALPHA_ | 26.167 |
| r1 min. | 3,3 mm |
| ra max. | 3,5 mm |
| Oil rpm | 4000 |
| outer r | 3.3 |
| hidYobi | 72200/72487 |
| GRS rpm | 3000 |
| inner r | 3.5 |
| hidTable | ecat_NSTPRI |
| inner ra | 3.5 |
| outer rb | 3.3 |
| ra1 max. | 3,3 mm |
| Size (mm) | 50.8x123.825x36.512 |
| SHOG_yobi | 72200R/72487R |
| Prod_Type3 | TRBSR_ID_A |
| Width (mm) | 36,512 |
| Bearing number | 72200/72487 |
| Bore Diameter (mm) | 50,8 |
| Outer Diameter (mm) | 123,825 |
| Calculation factor (e) | 0,74 |
| | |

| | |
|-------------------------------|------------|
| (Oil) Lubrication Speed | 4000 r/min |
| Calculation factor (Y0) | 0,45 |
| (Grease) Lubrication Speed | 3000 r/min |
| Basic static load rating (C0) | 160 kN |
| Basic dynamic load rating (C) | 143 kN |