



Bearing No. 368A/362A

e	0.32
d	50,8 mm
D	88,9 mm
T	20,638 mm
B	22,225 mm
C	16,513 mm
a	16,6 mm
Da	81 mm
B_	22.225
Db	84 mm
da	62 mm
Y0	1
db	56 mm
C0	85
D_	88.9
Z_	17
C_	16.513
Y1	1.9
DE_	79.078
SLR	14.2
D_a	81
DI_	58.43
DA1	10.871
DA2	10.09
CUP	0.166
DA_	10.483
D_b	84
RAr	196.722
SDM_	68.786
KBRG	3161

yobi	368A/362A
CONE	0.338
ALP21	24
ALP22	4
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	10
r min.	3,5 mm
LangID	1
Weight	0,504 Kg
ALPHA_	12.033
r1 min.	1,3 mm
ra max.	3,5 mm
Oil rpm	5600
outer r	1.3
hidYobi	368A/362A
GRS rpm	4000
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	50.8x88.9x20.638
SHOG_yobi	368AR/362AR
Prod_Type3	TRBSR_ID_A
Width (mm)	20,638
Bearing number	368A/362A
Bore Diameter (mm)	50,8
Outer Diameter (mm)	88,9
Calculation factor (e)	0,32

(Oil) Lubrication Speed	5600 r/min
Calculation factor (Y0)	1
(Grease) Lubrication Speed	4000 r/min
Basic static load rating (C0)	85 kN
Basic dynamic load rating (C)	73 kN