



Bearing No. TRA0607R

C	14 mm
e	0.55
d	30 mm
D	72 mm
T	20,75 mm
B	19 mm
a	18,6 mm
Y0	0.60
Y1	1.10
Cu	8.10
Cr	71.2
C0r	55.6
a(mm)	18.6
r min.	1,5 mm
da max	39 mm
Da min	58 mm
r(min)	1.5
Weight	0,405 Kg
r1(min)	1.5
db(max)	39
da(min)	38.5
Sb(min)	4.5
Da(max)	63.5
Sa(min)	3
Da(min)	58
ra(max)	1.5
rb(max)	1.5
Db(min)	68
rb max.	1,5 mm
ra max.	1,5 mm

Db min.	68 mm
Da max.	63,5 mm
da min.	38,5 mm
r2 min.	1,5 mm
Oil lub.	7900
Size (mm)	30x72x20.75
Width (mm)	20,75
Bearing No.	TRA0607R
Grease lub.	5900
Bearing number	TRA0607R
(Refer.)Mass(kg)	0.405
Bore Diameter (mm)	30
Outer Diameter (mm)	72
Calculation factor (e)	0,55
Calculation factor (Y0)	0,6
(Oil) Lubrication Speed	7900 r/min
(Grease) Lubrication Speed	5900 r/min
Basic static load rating (C0)	55,6 kN
Basic dynamic load rating (C)	56,9 kN