



Bearing No. 7200 ACD/P4A

D	30 mm
d	10 mm
B	9 mm
a	9.3 mm
Ball - z	10
Size (mm)	30x10x9
Width (mm)	9
Mass bearing	0.032 kg
d_n	18.3 mm
d_n	18.3 mm
D_1	23.1 mm
d_1	17.3 mm
d_2	17.3 mm
D_1	23.1 mm
d_2	17.3 mm
d_1	17.3 mm
Bearing number	7200 ACD/P4A
Preload class B	45 N/micron
Preload class A	35 N/micron
Preload class D	78 N/micron
Preload class C	59 N/micron
G_{ref}	0.357 cm ³
Number of balls z	10
Bore Diameter (mm)	30
r_b max.	0.3 mm
r_a max.	0.6 mm
D_b max.	27.6 mm
D_a max.	25.8 mm
d_a min.	14.2 mm

d _b min.	14.2 mm
Outer Diameter (mm)	10
D _b - max.	27.6 mm
d _b - min.	14.2 mm
Ball - D _w	4.762 mm
r _{1,2} min.	0.6 mm
r _{3,4} min.	0.3 mm
d _a - min.	14.2 mm
r _a - max.	0.6 mm
D _a - max.	25.8 mm
r _b - max.	0.3 mm
Calculation factor f	1.02
Calculation factor e	0.68
r _{1,2} - min.	0.6 mm
r _{3,4} - min.	0.3 mm
Calculation factor - e	0.68
Calculation factor - f	1.02
Ball diameter D _w	4.762 mm
Basic dynamic load rating C	4.36 kN
Preload class C G _C	108 N
Preload class B G _B	54 N
Preload class A G _A	27 N
Preload class D G _D	216 N
Basic dynamic load rating - C	4.4 kN
Preload class B - G _B	54 N
Preload class D - G _D	216 N
Preload class C - G _C	108 N
Preload class A - G _A	27 N
Fatigue load limit P _u	0.078 kN
Calculation factor f ₁	0.99

Calculation factor f_{2A}	1
Calculation factor f_{2C}	1.02
Calculation factor f_{2B}	1.01
Calculation factor f_{2D}	1.05
Calculation factor f_{HC}	1
Calculation factor - X_2	0.67
Calculation factor - f_1	0.99
Calculation factor - Y_1	0.92
Limiting speed for oil lubrication	80000 mm/min
Calculation factor - Y_0	0.76
Fatigue load limit - P_u	0.078 kN
Calculation factor - Y_2	1.41
Calculation factor - f_{HC}	1
Calculation factor - f_{2A}	1
Calculation factor - f_{2C}	1.02
Calculation factor - f_{2B}	1.01
Calculation factor - f_{2D}	1.05
Limiting speed for grease lubrication	53000 r/min
Basic static load rating C_0	1.86 kN
Static axial stiffness, preload class B	45 N/ μm
Attainable speed for grease lubrication	53000 r/min
Static axial stiffness, preload class D	78 N/ μm
Static axial stiffness, preload class C	59 N/ μm
Static axial stiffness, preload class A	35 N/ μm
Basic static load rating -	1.9 kN

C_0	
Attainable speed for oil-air lubrication	80000 r/min
Reference grease quantity G_{ref}	0.357 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67