



Bearing No. 7409B

a	49.5 mm
d	45 mm
D	120 mm
B	29 mm
C	29 mm
Cr	106
f0	-
Cu	4.00
C0r	55.5
Noun	Bearing
Bore	1.772 Inch 45 Millimeter
Width	1.142 Inch 29 Millimeter
a(mm)	49.5
r min.	2 mm
UNSPSC	31171531
r(min)	2
Weight	1.55 Kg
da(min)	55
ra max.	2 mm
r1 min.	1 mm
Da max.	110 mm
r1(min)	1
da min.	55 mm
Da(max)	110
ra(max)	2
Category	Angular Contact Ball Bearing
Oil lub.	5200
Inventory	0.0

Enclosure	Open
Size (mm)	45x120x29
Snap Ring	No
Width (mm)	29
Grease lub.	3800
Bearing No.	7409B
Flush Ground	No
Contact Angle	40 Degree
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7409B
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	1.55
Outside Diameter	4.724 Inch 120 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	45MM Bore; 120MM Outside Diameter; 29MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	45

Outer Diameter (mm)	120
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	4800 r/min
Maximum Capacity / Filling Slot	No