



Bearing No. 3782/3720

| | |
|---------------------------------|---------------------|
| R | 3,6 mm |
| d | 44,45 mm |
| D | 93,264 mm |
| T | 30,162 mm |
| B | 30,302 mm |
| C | 23,812 mm |
| r | 3,3 mm |
| Da | 88 mm |
| Ab | 0,9 mm |
| Aa | 1,9 mm |
| Db | 82 mm |
| da | 52 mm |
| db | 58 mm |
| a - | 8,1 mm |
| Weight | 0,96 Kg |
| Size (mm) | 44.45x93.264x30.162 |
| Width (mm) | 30,162 |
| Factor (K) | 1,73 |
| Factor (G1) | 49,9 |
| Factor (Cg) | 0,0233 |
| Factor (G2) | 14,5 |
| Bearing number | 3782/3720 |
| Bore Diameter (mm) | 44,45 |
| Outer Diameter (mm) | 93,264 |
| Calculation factor (e) | 0,34 |
| Basic static load rating (C0) | 153 kN |
| Basic dynamic load rating (C1) | 113 kN |
| Basic dynamic load rating (C90) | 29,3 |

| | |
|----------------------------------|----|
| Basic dynamic load rating (Ca90) | 17 |
|----------------------------------|----|