




Bearing No. 6206-2Z/VA228

D	62 mm
d	30 mm
B	16 mm
C	16 mm
d1	40,3 mm
D2	54,1 mm
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
Weight	0,2 Kg
UNSPSC	31171504
series:	62
r1 min.	1 mm
r2 min.	1 mm
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Size (mm)	30x62x16
Enclosure	2 Metal Shields
Width (mm)	16
bore type:	Round
Mass bearing	0.21 kg
Weight / LBS	0.463
maximum rpm:	190 RPM
Inch - Metric	Metric
Cage Material	Graphite
Temperature -	150 to +350 °
Product Group	B00308
closure type:	Double Shielded
bore diameter:	30 mm

Limiting speed	190 r/min
overall width:	16 mm
fillet radius:	1 mm
cage material:	Graphite
Bearing number	6206-2Z/VA228
Keyword String	Ball
Other Features	Deep Groove Extreme Temperature Variant
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Coronet Cage Internal Special Features; C0-Medium Internal Clear
Manufacturer URL	http://www.skf.com
Outside Diameter	2.441 Inch 62 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
outer ring width:	16 mm
Weight / Kilogram	0.21
Manufacturer Name	SKF
outside diameter:	62 mm
precision rating:	Not Rated
Bore Diameter (mm)	30
Internal Clearance	C0-Medium
r _a max.	1 mm
D _a max.	56.4 mm
	40.3 mm

q^a max.	
-------------------------------	--

d _a min.	35.6 mm
internal clearance:	C0
Outer Diameter (mm)	62
Minimum Buy Quantity	N/A
resistance features:	Corrosion Resistant, Extreme Temperature
r _{1,2} min.	1 mm
D ₂ ?	54.06 mm
static load capacity:	11.2 kN
d ₁ ?	40.36 mm
row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6206-2Z/VA228
Internal Special Features	Coronet Cage
Basic dynamic load rating C	20.3 kN
Limiting temperature T max.	350 °C
operating temperature range:	-240 to +660 °F
Basic static load rating (C0)	11,2 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C ₀	11.2 kN