



### Bearing No. 7336BDT

D	380 mm
a	80.0 mm
C	75 mm
B	75 mm
d	180 mm
r1	1.5 mm
2B	150 mm
Width	75 mm
r min.	4 mm
Weight	41.3 Kg
ra max.	1.5 mm
r1 min.	1.5 mm
da min.	189 mm
Da max.	371 mm
ra (max)	3 mm
da1 (min)	198 mm
Bore Size	180 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	1.5 mm
Size (mm)	180x380x75
da2 (min)	189 mm
Da2 (max)	371 mm
Da1 (max)	362 mm
Width (mm)	75
Configuration	Duplex
Bearing number	7336BDT
Angle (?)	40 °
Outside Diameter	380 mm
Static Load Rating	1,010,000 N

Bore Diameter (mm)	180
Dynamic Load Rating	625,000 N
Outer Diameter (mm)	380
Limiting Speed - Oil	1,500 rpm
Fillet Radius/Chamfer	4 mm
Limiting Speed - Grease	1,100 rpm
(Grease) Lubrication Speed	1100 r/min
Basic dynamic load rating (C)	625 kN
Basic static load rating (C0)	1010 kN