



Bearing No. 7203 BECBM

a	18 mm
d	17 mm
D	40 mm
B	12 mm
Noun	Bearing
Bore	0.669 Inch 17 Millimeter
Width	0.472 Inch 12 Millimeter
UNSPSC	31171531
weight:	0.14 lb
series:	7200
Category	Angular Contact Ball Bearing
Snap Ring	No
Inventory	0.0
Size (mm)	40x17x12
Enclosure	Open
bore type:	Round
Width (mm)	12
Flush Ground	Yes
Weight / LBS	0.1609
Mass bearing	0.065 kg
maximum rpm:	28000 rpm
Product Group	B00308
Inch - Metric	Metric
Contact Angle	40 Degree
Cage Material	Brass
D ₁	31.15 mm
d ₂	21.66 mm
d ₁	26.25 mm

closure type:	Open
bore diameter:	17 mm
cage material:	Brass
Keyword String	Angular Contact
contact angle:	40 °
fillet radius:	0.6 mm
overall width:	12 mm
Bearing number	7203 BECBM
Other Features	Normal Axial Internal Clearance
Limiting speed	22000 r/min
Precision Class	ABEC 1 ISO P0
Reference speed	22000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Outside Diameter	1.575 Inch 40 Millimeter
Manufacturer URL	http://www.skf.com
Long Description	17MM Bore; 40MM Outside Diameter; 12MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; CB; Brass Cage; 40 Degree; 1 (Single); Universa
Weight / Kilogram	0.073
outside diameter:	40 mm
bearing material:	Steel
Manufacturer Name	SKF
D _a max.	35.8 mm
Bore Diameter (mm)	40
d _a min.	21.2 mm

D_b max.	35.8 mm
r_a max.	0.6 mm
r_b max.	0.6 mm
Number of Bearings	1 (Single)
Internal Clearance	CB
Outer Diameter (mm)	17
D_b - max.	35.8 mm
$r_{3,4}$ min.	0.6 mm
$r_{1,2}$ min.	0.6 mm
Calculation factor A	0.000625
Calculation factor e	1.14
Minimum Buy Quantity	N/A
Calculation factor X	0.57
D_a - max.	35.8 mm
d_a - min.	21.2 mm
r_a - max.	0.6 mm
maximum temperature:	257 °F
Mounting Arrangement	Universal
r_b - max.	0.6 mm
d_1 ?	26.25 mm
row type & fill slot:	Single-Row Non-Fill Slot
D_1 ?	31.15 mm
d_2 ?	21.66 mm
$r_{3,4}$ - min.	0.6 mm
$r_{1,2}$ - min.	0.6 mm
Calculation factor - X	0.35
Calculation factor - e	1.14
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
Manufacturer Item Number	7203 BECBM
manufacturer upc number:	7316571192635

manufacturer product page:	Click here
Basic dynamic load rating C	11 kN
radial static load capacity:	5.85 kN
Basic dynamic load rating - C	11 kN
radial dynamic load capacity:	11 kN
Maximum Capacity / Filling Slot	No
Calculation factor k_r	0.095
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor Y_0	0.52
Fatigue load limit P_u	0.25 kN
Calculation factor - Y_0	0.26
Fatigue load limit - P_u	0.25 kN
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Calculation factor - k_a	1.4
Calculation factor - k_r	0.095
Basic static load rating C_0	5.85 kN
Basic static load rating - C_0	5.8 kN