



### Bearing No. 6206LLB

D	62 mm
d	30 mm
B	16 mm
C	16 mm
Noun	Bearing
Bore	1.181 Inch   30 Millimeter
r min.	1 mm
da max	39 mm
UNSPSC	31171504
Weight	0,199 Kg
Da max.	57 mm
ra max.	1 mm
da min.	35 mm
series:	62
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	30x62x16
bore type:	Round
Width (mm)	16
Weight / LBS	0.439
maximum rpm:	13000 RPM
closure type:	Double Sealed
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Keyword String	Ball
Other Features	Deep Groove   Non-Friction Nitrile Rubber

	Seal
Enclosure Type	Non-Contact Seal
Bearing number	6206LLB
bore diameter:	30 mm
overall width:	16 mm
cage material:	Steel
fillet radius:	1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
finish/coating:	Uncoated
Outside Diameter	2.441 Inch   62 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.63 Inch   16 Millimeter
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
bearing material:	High Carbon Chrome Steel
outside diameter:	62 mm
inner ring width:	16 mm
Manufacturer Name	NTN
Weight / Kilogram	0.198
outer ring width:	16 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	30
Internal Clearance	C0-Medium

snap ring included:	Without Snap Ring
Outer Diameter (mm)	62
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	11300 N
maximum rpm (grease):	11000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	19500 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6206LLB
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
(Grease) Lubrication Speed	11 000 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	19,5 kN
Basic static load rating (C0)	11,3 kN
Maximum Capacity / Filling Slot	No