



Bearing No. 6206LLU

C	16 mm
d	30 mm
D	62 mm
B	16 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
Weight	0,199 Kg
da max	39 mm
UNSPSC	31171504
r min.	1 mm
da min.	35 mm
ra max.	1 mm
series:	62
Da max.	57 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	30x62x16
Inventory	0.0
Snap Ring	No
Width (mm)	16
bore type:	Round
maximum rpm:	7300 RPM
Weight / LBS	0.438
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	30 mm
Keyword String	Ball

overall width:	16 mm
cage material:	Steel
fillet radius:	1 mm
Bearing number	6206LLU
Enclosure Type	Contact Seal
Reference speed	7 300 r/min
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Manufacturer URL	http://www.ntnamerica.com
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
outside diameter:	62 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.198
inner ring width:	16 mm
outer ring width:	16 mm
Manufacturer Name	NTN
Bore Diameter (mm)	30
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	62

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	7300 rpm
static load capacity:	11300 N
dynamic load capacity:	19500 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6206LLU/5C
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	11,3 kN
Basic dynamic load rating (C)	19,5 kN
Maximum Capacity / Filling Slot	No