



Bearing No. 7203DT

D	40 mm
a	2.2 mm
C	12 mm
B	12 mm
d	17 mm
r1	0.3 mm
2B	24 mm
Width	12 mm
r min.	0.6 mm
Weight	0.070 Kg
ra max.	0.3 mm
r1 min.	0.3 mm
da min.	19 mm
Da max.	37.4 mm
ra (max)	0.6 mm
da1 (min)	22 mm
Bore Size	17 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.3 mm
Size (mm)	17x40x12
da2 (min)	19 mm
Da2 (max)	37.4 mm
Da1 (max)	35 mm
Width (mm)	12
Configuration	Duplex
Bearing number	7203DT
Angle (?)	30 °
Outside Diameter	40 mm
Static Load Rating	13,200 N

Bore Diameter (mm)	17
Dynamic Load Rating	19,400 N
Outer Diameter (mm)	40
Limiting Speed - Oil	17,000 rpm
Fillet Radius/Chamfer	0.6 mm
Limiting Speed - Grease	13,000 rpm
(Grease) Lubrication Speed	13000 r/min
Basic dynamic load rating (C)	19,4 kN
Basic static load rating (C0)	13,2 kN