



Bearing No. 6206N

a	3,28 mm
r	1
d	30 mm
D	62 mm
B	16 mm
C	16 mm
b	1,9 mm
fo	13.8
B_	16
ra	1
C0	11.3
D1	59,61 mm
D_	62
Z_	9
rn	0,5 mm
ro	0.6
DE_	56.025
SRI	4.81
D_a	57
DA_	9.525
SRE	5
DI_	36.975
yobi	6206N
mass	0.199
SBRG	2
bomp	0
KBRG	6101
SREX	0.04
SREN	0
SRIN	0

SDM_	46.5
SRIX	0.02
ALPHA_	0
r min.	1 mm
C_conv	19500
da max	38,5 mm
da min	35
Weight	0,199 Kg
LangID	1
ra max.	1 mm
Da max.	57 mm
Oil rpm	13000
da min.	35 mm
r0 max.	0,6 mm
hidYobi	6206N
GRS rpm	11000
hidTable	ecat_NSRDGB
Size (mm)	30x62x16
Prod_Type3	DGBB_SR_N_OT
Width (mm)	16
Bearing number	6206N
Bore Diameter (mm)	30
Outer Diameter (mm)	62
(Oil) Lubrication Speed	13 000 r/min
(Grease) Lubrication Speed	11 000 r/min
Basic dynamic load rating (C)	19,5 kN
Basic static load rating (C0)	11,3 kN