



Bearing No. 6206NR

f	1,7 mm
r	1
d	30 mm
D	62 mm
B	16 mm
C	16 mm
a	3,28 mm
b	1,9 mm
D1	59,61 mm
fo	13.8
C0	11.3
ra	1
D2	67,7 mm
B_	16
Cy	4.6
Dx	68.5
rn	0,5 mm
ro	0.6
D_	62
Z_	9
SRE	5
D_a	57
SRI	4.81
DE_	56.025
DA_	9.525
DI_	36.975
bomp	0
SREX	0.04
yobi	6206NR
SBRG	2

KBRG	6101
SDM_	46.5
mass	0.199
Bore	1.181 Inch 30 Millimeter
SRIX	0.02
SRIN	0
SREN	0
Noun	Bearing
UNSPSC	31171504
LangID	1
r min.	1 mm
da max	38,5 mm
C_conv	19500
ALPHA_	0
Weight	0,199 Kg
da min	35
ra max.	1 mm
Da max.	57 mm
hidYobi	6206NR
Oil rpm	13000
da min.	35 mm
GRS rpm	11000
r0 max.	0,6 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	Yes
Size (mm)	30x62x16
Inventory	2.0
Enclosure	Open
bore type:	Round
Width (mm)	16
Prod_Type3	DGBB_SR_NR_OT

Weight / LBS	0.201
closure type:	Open
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6206NR
Keyword String	Ball
bore diameter:	30 mm
overall width:	16 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
outside diameter:	62 mm
Weight / Kilogram	0.19
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	62
internal clearance:	Normal Clearance
snap ring included:	With Snap Ring
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	13 000 r/min

manufacturer upc number:	029176014468
Manufacturer Item Number	6206NR
Internal Special Features	No
(Grease) Lubrication Speed	11 000 r/min
Basic static load rating (C0)	11,3 kN
Basic dynamic load rating (C)	19,5 kN
Maximum Capacity / Filling Slot	No