



Bearing No. 6206VV

D	62 mm
d	30 mm
B	16 mm
C	16 mm
r	1
Z_	9
B_	16
D_	62
ra	1
C0	11.3
fo	13.8
DI_	36.975
SRI	4.81
D_a	57
DE_	56.025
DA_	9.525
SRE	5
SRIN	0
SBRG	2
yobi	6206VV
SDM_	46.5
SREX	0.04
KBRG	6151
bomp	0
mass	0.199
Bore	1.181 Inch 30 Millimeter
SRIX	0.02
SREN	0
Noun	Bearing

ALPHA_	0
da min	35
LangID	1
r min.	1 mm
UNSPSC	31171504
da max	38,5 mm
C_conv	19500
Weight	0,199 Kg
ra max.	1 mm
hidYobi	6206VV
GRS rpm	11000
da min.	35 mm
Da max.	57 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	30x62x16
Enclosure	2 Seals
Inventory	0.0
Width (mm)	16
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.199
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6206VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	2.441 Inch 62 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter

Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.09
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6206VV
Internal Special Features	No
(Grease) Lubrication Speed	11 000 r/min
Basic static load rating (C0)	11,3 kN
Basic dynamic load rating (C)	19,5 kN
Maximum Capacity / Filling Slot	No