



Bearing No. 6206ZZ

D	62 mm
d	30 mm
B	16 mm
C	16 mm
rn	0,5 mm
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
UNSPSC	31171504
da max	39 mm
Weight	0,199 Kg
r min.	1 mm
da min.	35 mm
Da max.	57 mm
ra max.	1 mm
series:	62
Category	Single Row Ball Bearing
Size (mm)	30x62x16
Enclosure	2 Metal Shields
Inventory	191.0
Snap Ring	No
bore type:	Round
Width (mm)	16
Weight / LBS	0.439
maximum rpm:	13000 RPM
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6206ZZ
bore diameter:	30 mm
overall width:	16 mm
cage material:	Steel
fillet radius:	1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0.204
outer ring width:	16 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	16 mm
outside diameter:	62 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium
Bore Diameter (mm)	30

Outer Diameter (mm)	62
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	11000 rpm
static load capacity:	11300 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	19500 N
Internal Special Features	No
(Grease) Lubrication Speed	11 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	11,3 kN
Basic dynamic load rating (C)	19,5 kN
Maximum Capacity / Filling Slot	No