



Bearing No. 7204 ACD/P4A

a	15 mm
d	20 mm
D	47 mm
B	14 mm
Noun	Bearing
Bore	0.787 Inch 20 Millimeter
Width	0.551 Inch 14 Millimeter
UNSPSC	31171531
Preload	None
Ball - z	11
Category	Precision Ball Bearings
Size (mm)	47x20x14
Enclosure	Open
Inventory	0.0
Width (mm)	14
Weight / LBS	0.238
Flush Ground	No
Mass bearing	0.1 kg
d_1	29.1 mm
d_2	29.1 mm
D_1	38.7 mm
Inch - Metric	Metric
Cage Material	Phenolic
d_n	31.1 mm
Contact Angle	25 Degree
Product Group	B04270
Raceway Style	1 Rib Outer Ring
d_1	29.1 mm
d	31.1 mm

n	
D ₁	38.7 mm
d ₂	29.1 mm
Bearing number	7204 ACD/P4A
Other Features	Single Row Angular Contact Super Precision High Capacity Basic Design
Keyword String	Ball Angular Contact
Material - Ball	Steel
Precision Class	ABEC 7 ISO P4
G _{ref}	1.539 cm ³
Preload class D	135 N/micron
Preload class C	102 N/micron
Preload class B	79 N/micron
Preload class A	61 N/micron
Rolling Element	Ball Bearing
Outside Diameter	1.85 Inch 47 Millimeter
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 1 (Single) Bearing; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Outer Ring Race
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0
Manufacturer Name	SKF
Number of balls z	11
r _b max.	0.3 mm
Bore Diameter (mm)	47
D _a max.	41.4 mm

D_b max.	44.6 mm
d_a min.	25.6 mm
r_a max.	1 mm
Number of Bearings	1 (Single)
d_b min.	25.6 mm
Outer Diameter (mm)	20
d_a - min.	25.6 mm
$r_{1,2}$ min.	1 mm
d_b - min.	25.6 mm
Calculation factor f	1.03
$r_{3,4}$ min.	0.3 mm
Calculation factor e	0.68
D_a - max.	41.4 mm
Ball - D_w	7.938 mm
D_b - max.	44.6 mm
Minimum Buy Quantity	N/A
r_b - max.	0.3 mm
r_a - max.	1 mm
Calculation factor - e	0.68
Calculation factor - f	1.03
$r_{1,2}$ - min.	1 mm
$r_{3,4}$ - min.	0.3 mm
Harmonized Tariff Code	8482.10.50.28
Manufacturer Item Number	7204 ACD/P4A
Ball diameter D_w	7.938 mm
Basic dynamic load rating C	11.4 kN
Preload class A G_A	70 N
Preload class D G_D	560 N
Preload class C G_C	280 N
Basic dynamic load rating - C	11.4 kN

Preload class B G_B	140 N
Preload class C - G_C	280 N
Preload class A - G_A	70 N
Preload class D - G_D	560 N
Preload class B - G_B	140 N
Calculation factor f_1	0.99
Fatigue load limit P_u	0.236 kN
Calculation factor f_{2C}	1.02
Calculation factor f_{HC}	1
Calculation factor f_{2B}	1.01
Calculation factor f_{2D}	1.05
Calculation factor f_{2A}	1
Calculation factor - Y_0	0.76
Calculation factor - Y_2	1.41
Fatigue load limit - P_u	0.236 kN
Limiting speed for oil lubrication	48000 mm/min
Calculation factor - X_2	0.67
Calculation factor - Y_1	0.92
Calculation factor - f_1	0.99
Calculation factor - f_{2D}	1.05
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.01
Calculation factor - f_{2C}	1.02
Calculation factor - f_{HC}	1
Limiting speed for grease lubrication	32000 r/min
Basic static load rating C_0	5.6 kN
Attainable speed for grease lubrication	32000 r/min

Static axial stiffness, preload class D	135 N/ μ m
Static axial stiffness, preload class C	102 N/ μ m
Static axial stiffness, preload class B	79 N/ μ m
Static axial stiffness, preload class A	61 N/ μ m
Attainable speed for oil-air lubrication	48000 r/min
Basic static load rating - C_0	5.6 kN
Reference grease quantity G_{ref}	1.539 cm ³
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67