



Bearing No. 388A/382A

e	0.35
d	57,531 mm
D	96,838 mm
T	21 mm
B	21,946 mm
C	15,875 mm
a	17,6 mm
Da	89 mm
B_	21.946
Db	92 mm
da	69 mm
Y0	0.93
db	63 mm
C0	100
D_	96.838
Z_	19
C_	15.875
Y1	1.7
DE_	86.801
SLR	14.35
D_a	89
DI_	66.334
DA1	10.533
DA2	9.765
CUP	0.179
DA_	10.3
D_b	92
RAr	195.758
SDM_	76.475
KBRG	3161

yobi	388A/382A
CONE	0.416
ALP21	26
ALP22	34
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	5
r min.	3,5 mm
LangID	1
Weight	0,595 Kg
ALPHA_	13.283
r1 min.	0,8 mm
ra max.	3,5 mm
Oil rpm	5000
outer r	0.8
hidYobi	388A/382A
GRS rpm	3600
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	0.8
ra1 max.	0,8 mm
Size (mm)	57.531x96.838x21
SHOG_yobi	388A/382A
Prod_Type3	TRBSR_ID_A
Width (mm)	21
Bearing number	388A/382A
Bore Diameter (mm)	57,531
Outer Diameter (mm)	96,838
Calculation factor (e)	0,35

(Oil) Lubrication Speed	5000 r/min
Calculation factor (Y0)	0,93
(Grease) Lubrication Speed	3600 r/min
Basic static load rating (C0)	100 kN
Basic dynamic load rating (C)	80,5 kN