



Bearing No. 7204CDF

| | |
|--------------------|------------------|
| C | 14 mm |
| d | 20 mm |
| B | 14 mm |
| D | 47 mm |
| r1 | 0.6 mm |
| 2B | 28 mm |
| a - | 3.1 mm |
| Width | 14 mm |
| r min. | 1 mm |
| Weight | 0.110 Kg |
| ra max. | 0.6 mm |
| r1 min. | 0.6 mm |
| da min. | 26 mm |
| Da max. | 43.4 mm |
| ra (max) | 1 mm |
| da1 (min) | 26 mm |
| Bore Size | 20 mm |
| Enclosure | Open |
| Bore Type | Cylindrical Bore |
| ra1 (max) | 0.6 mm |
| Size (mm) | 20x47x14 |
| da2 (min) | 26 mm |
| Da2 (max) | 43.4 mm |
| Da1 (max) | 41 mm |
| Width (mm) | 14 |
| Configuration | Duplex |
| Bearing number | 7204CDF |
| Angle (?) | 15 ° |
| Outside Diameter | 47 mm |
| Static Load Rating | 16,300 N |
| | |

| | |
|-------------------------------|-------------|
| Bore Diameter (mm) | 20 |
| Dynamic Load Rating | 23,800 N |
| Outer Diameter (mm) | 47 |
| Limiting Speed - Oil | 26,000 rpm |
| Fillet Radius/Chamfer | 1 mm |
| Limiting Speed - Grease | 19,000 rpm |
| (Grease) Lubrication Speed | 19000 r/min |
| Basic dynamic load rating (C) | 23,8 kN |
| Basic static load rating (C0) | 16,3 kN |