



VA201



2Z/VA201



2Z/VA208



2Z/VA228

Bearing No. 6207/VA201

| | |
|----------------|----------------------------|
| D | 72 mm |
| d | 35 mm |
| B | 17 mm |
| C | 17 mm |
| d1 | 46,9 mm |
| D2 | 62,7 mm |
| Noun | Bearing |
| Bore | 1.378 Inch 35 Millimeter |
| Weight | 0,29 Kg |
| UNSPSC | 31171504 |
| series: | 62 |
| r1 min. | 1,1 mm |
| r2 min. | 1,1 mm |
| Category | Single Row Ball Bearing |
| Enclosure | Open |
| Inventory | 0.0 |
| Size (mm) | 35x72x17 |
| Snap Ring | No |
| bore type: | Round |
| Width (mm) | 17 |
| Weight / LBS | 0.29 |
| maximum rpm: | 160 RPM |
| Mass bearing | 0.29 kg |
| Product Group | B00308 |
| Cage Material | Steel |
| closure type: | Open |
| Inch - Metric | Metric |
| Temperature - | 30 to +250 ° |
| overall width: | 17 mm |
| | |

| | |
|---------------------|--|
| bore diameter: | 35 mm |
| cage material: | Steel |
| Limiting speed | 160 r/min |
| fillet radius: | 1.1 mm |
| Bearing number | 6207/VA201 |
| Keyword String | Ball |
| Other Features | Deep Groove Extreme Temperature Variant |
| finish/coating: | Uncoated |
| Rolling Element | Ball Bearing |
| Precision Class | ABEC 1 ISO P0 |
| Long Description | 35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Features; C0-M |
| Manufacturer URL | http://www.skf.com |
| Outer Race Width | 0.669 Inch 17 Millimeter |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outside Diameter | 2.835 Inch 72 Millimeter |
| Manufacturer Name | SKF |
| Weight / Kilogram | 0.291 |
| outer ring width: | 17 mm |
| precision rating: | Not Rated |
| outside diameter: | 72 mm |
| Internal Clearance | C0-Medium |
| d _a min. | 42 mm |
| D _a max. | 65 mm |
| r _a max. | 1 mm |

| | |
|---|---|
| Bore Diameter (mm) | 35 |
| snap ring included: | Without Snap Ring |
| internal clearance: | C0 |
| Outer Diameter (mm) | 72 |
| Minimum Buy Quantity | N/A |
| r _{1,2} min. | 1.1 mm |
| resistance features: | Corrosion Resistant, Extreme Temperature |
| row type & fill slot: | Single Row Non-Fill Slot |
| static load capacity: | 15.3 kN |
| d ₁ ? | 46.94 mm |
| D ₂ ? | 62.69 mm |
| Harmonized Tariff Code | 8482.10.50.68 |
| Manufacturer Item Number | 6207/VA201 |
| Internal Special Features | Polyalkylene Glycol/Graphite Mixture Filled |
| Basic dynamic load rating C | 27 kN |
| Limiting temperature T max. | 250 °C |
| operating temperature range: | -20 to +480 °F |
| Basic static load rating (C0) | 15,3 kN |
| Maximum Capacity / Filling Slot | No |
| Basic static load rating C ₀ | 15.3 kN |