



Bearing No. 6207DDU

r	1.1
d	35 mm
D	72 mm
B	17 mm
C	17 mm
D_	72
C0	15.3
Z_	9
ra	1
fo	13.8
B_	17
DI_	42.388
SRI	5.61
SRE	5.89
DE_	64.612
DA_	11.112
D_a	65.5
KBRG	6161
SBRG	2
SRIN	0
bomp	0
SREX	0.05
yobi	6207DDU
SRIX	0.025
mass	0.284
SDM_	53.5
SREN	0
Bore	1.378 Inch 35 Millimeter
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	41.5
r min.	1,1 mm
Weight	0,284 Kg
ALPHA_	0
C_conv	25700
da max	44,5 mm
GRS rpm	6300
Da max.	65,5 mm
ra max.	1 mm
da min.	41,5 mm
hidYobi	6207DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	35x72x17
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	17
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.63492
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6207DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outer Race Width	0.669 Inch 17 Millimeter
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	2.835 Inch 72 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.288
Internal Clearance	C0-Medium
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6207DDU
Internal Special Features	No
(Grease) Lubrication Speed	6 300 r/min
Basic static load rating (C0)	15,3 kN
Basic dynamic load rating (C)	25,7 kN
Maximum Capacity / Filling Slot	No