



### Bearing No. 6207LLB

D	72 mm
d	35 mm
B	17 mm
C	17 mm
Bore	1.378 Inch   35 Millimeter
Noun	Bearing
da max	45 mm
UNSPSC	31171504
Weight	0,288 Kg
r min.	1,1 mm
da min.	41,5 mm
Da max.	65,5 mm
ra max.	1 mm
series:	62
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	35x72x17
Enclosure	2 Seals
Snap Ring	No
bore type:	Round
Width (mm)	17
Weight / LBS	0.635
maximum rpm:	11000 RPM
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Other Features	Deep Groove   Non-Friction Nitrile Rubber Seal

Enclosure Type	Non-Contact Seal
Keyword String	Ball
Bearing number	6207LLB
bore diameter:	35 mm
overall width:	17 mm
cage material:	Steel
fillet radius:	1.1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
Outside Diameter	2.835 Inch   72 Millimeter
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Weight / Kilogram	0.288
outer ring width:	17 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	17 mm
outside diameter:	72 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	35
Outer Diameter (mm)	72
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	9800 rpm
static load capacity:	15300 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	25700 N
Internal Special Features	No
(Grease) Lubrication Speed	9 800 r/min
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	15,3 kN
Basic dynamic load rating (C)	25,7 kN
Maximum Capacity / Filling Slot	No