



Bearing No. 6207N

a	3,28 mm
d	35 mm
D	72 mm
B	17 mm
C	17 mm
r	1.1
b	1,9 mm
D1	68,81 mm
ro	0.6
D_	72
ra	1
fo	13.8
B_	17
Z_	9
rn	0,5 mm
C0	15.3
D_a	65.5
DA_	11.112
SRE	5.89
DE_	64.612
DI_	42.388
SRI	5.61
SREN	0
Bore	1.378 Inch   35 Millimeter
mass	0.284
SRIN	0
SRIX	0.025
Noun	Bearing
bomp	0

yobi	6207N
SDM_	53.5
SREX	0.05
KBRG	6101
SBRG	2
LangID	1
C_conv	25700
Weight	0,284 Kg
da max	44,5 mm
r min.	1,1 mm
da min	41.5
UNSPSC	31171504
ALPHA_	0
hidYobi	6207N
GRS rpm	9500
Oil rpm	11000
Da max.	65,5 mm
ra max.	1 mm
da min.	41,5 mm
r0 max.	0,6 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	35x72x17
Snap Ring	Yes
Inventory	0.0
Enclosure	Open
Prod_Type3	DGBB_SR_N_OT
Width (mm)	17
Weight / LBS	0.6262
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308

Bearing number	6207N
Other Features	Deep Groove   With Snap Ring Groove
Keyword String	Ball
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outside Diameter	2.835 Inch   72 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Inner Race Width	0 Inch   0 Millimeter
Weight / Kilogram	0
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	11 000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	9 500 r/min
Basic static load rating (C0)	15,3 kN

Basic dynamic load rating (C)	25,7 kN
Maximum Capacity / Filling Slot	No