



Bearing No. 6207VV

D	72 mm
d	35 mm
B	17 mm
C	17 mm
r	1.1
Z_	9
B_	17
D_	72
ra	1
C0	15.3
fo	13.8
DI_	42.388
SRI	5.61
D_a	65.5
DE_	64.612
DA_	11.112
SRE	5.89
SRIN	0
SBRG	2
yobi	6207VV
SDM_	53.5
SREX	0.05
KBRG	6151
bomp	0
mass	0.284
Bore	1.378 Inch 35 Millimeter
SRIX	0.025
SREN	0
Noun	Bearing

ALPHA_	0
da min	41.5
LangID	1
r min.	1,1 mm
UNSPSC	31171504
da max	44,5 mm
C_conv	25700
Weight	0,284 Kg
ra max.	1 mm
hidYobi	6207VV
GRS rpm	9500
da min.	41,5 mm
Da max.	65,5 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	35x72x17
Enclosure	2 Seals
Inventory	0.0
Width (mm)	17
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.288
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6207VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	2.835 Inch 72 Millimeter
Outer Race Width	0.669 Inch 17

	Millimeter
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.28
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6207VV
Internal Special Features	No
(Grease) Lubrication Speed	9 500 r/min
Basic static load rating (C0)	15,3 kN
Basic dynamic load rating (C)	25,7 kN
Maximum Capacity / Filling Slot	No