



### Bearing No. 7205B

a	23.9 mm
d	25 mm
D	52 mm
B	15 mm
C	15 mm
Cr	18.4
f0	-
Cu	0.580
C0r	9.40
Noun	Bearing
Bore	0.984 Inch   25 Millimeter
Width	0.591 Inch   15 Millimeter
a(mm)	23.9
UNSPSC	31171531
r(min)	1
r min.	1 mm
Weight	0.135 Kg
da min.	30.5 mm
ra(max)	1
ra max.	1 mm
r1 min.	0.6 mm
Da max.	46.5 mm
da(min)	30.5
r1(min)	0.6
Da(max)	46.5
Category	Angular Contact Ball Bearing
Oil lub.	12000
Snap Ring	No

Enclosure	Open
Size (mm)	25x52x15
Inventory	0.0
Width (mm)	15
Bearing No.	7205B
Grease lub.	9600
Flush Ground	No
Contact Angle	40 Degree
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7205B
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	0.135
Outside Diameter	2.047 Inch   52 Millimeter
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Long Description	25MM Bore; 52MM Outside Diameter; 15MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	25

Outer Diameter (mm)	52
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	12 000 r/min
Maximum Capacity / Filling Slot	No