



Bearing No. 6207ZZ

D	72 mm
d	35 mm
B	17 mm
C	17 mm
rn	0,5 mm
Noun	Bearing
Bore	1.378 Inch 35 Millimeter
UNSPSC	31171504
da max	45 mm
Weight	0,288 Kg
r min.	1,1 mm
da min.	41,5 mm
Da max.	65,5 mm
ra max.	1 mm
series:	62
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	35x72x17
Inventory	0.0
Snap Ring	No
Width (mm)	17
bore type:	Round
Weight / LBS	0.626
maximum rpm:	11000 RPM
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Keyword String	Ball

Other Features	Deep Groove
Bearing number	6207ZZ
bore diameter:	35 mm
overall width:	17 mm
cage material:	Steel
fillet radius:	1.1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
Outer Race Width	0.669 Inch 17 Millimeter
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.ntnamerica.com
bearing material:	High Carbon Chrome Steel
outside diameter:	72 mm
inner ring width:	17 mm
Manufacturer Name	NTN
Weight / Kilogram	0
outer ring width:	17 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	35
Internal Clearance	C0-Medium

snap ring included:	Without Snap Ring
Outer Diameter (mm)	72
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	15300 N
maximum rpm (grease):	9800 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	25700 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6207ZZ
Internal Special Features	No
manufacturer product page:	Click here
(Grease) Lubrication Speed	9 800 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	25,7 kN
Basic static load rating (C0)	15,3 kN
Maximum Capacity / Filling Slot	No