



Bearing No. 7206 BECBM

D	62 mm
d	30 mm
B	16 mm
a	27.3 mm
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
Width	0.63 Inch 16 Millimeter
UNSPSC	31171531
Preload	Medium
series:	72
Category	Angular Contact Ball Bearing
Size (mm)	62x30x16
Inventory	0.0
Snap Ring	No
Enclosure	Open
Width (mm)	16
Flush Ground	Yes
Mass bearing	0.2 kg
maximum rpm:	14000 RPM
Weight / LBS	0.456
Cage Material	Brass
Contact Angle	40 Degree
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d ₂	36.13 mm
d ₁	42.65 mm
D ₁	50.1 mm

Other Features	Normal Axial Internal Clearance
fillet radius:	1 mm
contact angle:	40 °
overall width:	16 mm
cage material:	Brass
bore diameter:	30 mm
Keyword String	Angular Contact
Bearing number	7206 BECBM
Limiting speed	14000 r/min
Reference speed	14000 r/min
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 3 ISO P6
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Outside Diameter	2.441 Inch 62 Millimeter
Manufacturer URL	http://www.skf.com
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	62 mm
Manufacturer Name	SKF
Weight / Kilogram	0.21
outer ring width:	16 mm
r _b max.	0.6 mm
Number of Bearings	1 (Single)
r _a max.	1 mm
D _b max.	57.8 mm
D _a max.	56.4 mm

d_a min.	35.6 mm
Internal Clearance	CB
Bore Diameter (mm)	62
Outer Diameter (mm)	30
internal clearance:	C0
Mounting Arrangement	Universal
Calculation factor X	0.57
$r_{3,4}$ min.	0.6 mm
$r_{1,2}$ min.	1 mm
D_a - max.	56.4 mm
Calculation factor A	0.00377
Calculation factor e	1.14
d_a - min.	35.6 mm
r_b - max.	0.6 mm
Minimum Buy Quantity	N/A
r_a - max.	1 mm
D_b - max.	57.8 mm
D_1 ?	50.1 mm
d_2 ?	36.13 mm
d_1 ?	42.65 mm
row type & fill slot:	Single-Row Non-Fill Slot
Calculation factor - e	1.14
Calculation factor - X	0.35
$r_{1,2}$ - min.	1 mm
$r_{3,4}$ - min.	0.6 mm
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
Manufacturer Item Number	7206 BECBM
Basic dynamic load rating C	24 kN
radial static load capacity:	15.6 kN

Basic dynamic load rating - C	24 kN
radial dynamic load capacity:	24 kN
Maximum Capacity / Filling Slot	No
Calculation factor k_r	0.095
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor Y_0	0.52
Fatigue load limit P_u	0.655 kN
Calculation factor - k_a	1.4
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Fatigue load limit - P_u	0.655 kN
Calculation factor - Y_2	0.57
Calculation factor - k_r	0.095
Basic static load rating C_0	15.6 kN
Basic static load rating - C_0	15.6 kN