



**Bearing No. 7206BDB**

D	62 mm
a	11.3 mm
C	16 mm
B	16 mm
d	30 mm
r1	0.6 mm
2B	32 mm
Width	16 mm
r min.	1 mm
Weight	0.210 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	33 mm
Da max.	58.4 mm
ra (max)	1 mm
da1 (min)	36 mm
Bore Size	30 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	30x62x16
da2 (min)	33 mm
Da2 (max)	58.4 mm
Da1 (max)	56 mm
Width (mm)	16
Configuration	Duplex
Bearing number	7206BDB
Angle (?)	40 °
Outside Diameter	62 mm
Static Load Rating	27,900 N

Bore Diameter (mm)	30
Dynamic Load Rating	34,500 N
Outer Diameter (mm)	62
Limiting Speed - Oil	9,500 rpm
Fillet Radius/Chamfer	1 mm
Limiting Speed - Grease	7,000 rpm
(Grease) Lubrication Speed	7000 r/min
Basic dynamic load rating (C)	34,5 kN
Basic static load rating (C0)	27,9 kN