



Bearing No. 7206CDF

C	16 mm
d	30 mm
B	16 mm
D	62 mm
r1	0.6 mm
2B	32 mm
a -	2.7 mm
Width	16 mm
r min.	1 mm
Weight	0.210 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	36 mm
Da max.	58.4 mm
ra (max)	1 mm
da1 (min)	36 mm
Bore Size	30 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	30x62x16
da2 (min)	36 mm
Da2 (max)	58.4 mm
Da1 (max)	56 mm
Width (mm)	16
Configuration	Duplex
Bearing number	7206CDF
Angle (?)	15 °
Outside Diameter	62 mm
Static Load Rating	29,700 N

Bore Diameter (mm)	30
Dynamic Load Rating	37,500 N
Outer Diameter (mm)	62
Limiting Speed - Oil	19,000 rpm
Fillet Radius/Chamfer	1 mm
Limiting Speed - Grease	14,000 rpm
(Grease) Lubrication Speed	14000 r/min
Basic dynamic load rating (C)	37,5 kN
Basic static load rating (C0)	29,7 kN