



Bearing No. 7207BDF

D	72 mm
a	14.1 mm
C	17 mm
B	17 mm
d	35 mm
r1	0.6 mm
2B	34 mm
Width	17 mm
r min.	1.1 mm
Weight	0.295 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	40 mm
Da max.	67 mm
ra (max)	1 mm
da1 (min)	42 mm
Bore Size	35 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	35x72x17
da2 (min)	40 mm
Da2 (max)	67 mm
Da1 (max)	65 mm
Width (mm)	17
Configuration	Duplex
Bearing number	7207BDF
Angle (?)	40 °
Outside Diameter	72 mm
Static Load Rating	38,000 N

Bore Diameter (mm)	35
Dynamic Load Rating	45,500 N
Outer Diameter (mm)	72
Limiting Speed - Oil	8,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	6,000 rpm
(Grease) Lubrication Speed	6000 r/min
Basic dynamic load rating (C)	45,5 kN
Basic static load rating (C0)	38 kN