



Bearing No. 7208 BEGAY

D	80 mm
d	40 mm
B	18 mm
a	34 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
Width	0.709 Inch 18 Millimeter
UNSPSC	31171531
Preload	Light
series:	72
Category	Angular Contact Ball Bearing
Size (mm)	80x40x18
Enclosure	Open
Snap Ring	No
Inventory	0.0
Width (mm)	18
Weight / LBS	0.809
Flush Ground	Yes
Mass bearing	0.37 kg
maximum rpm:	10000 RPM
Product Group	B00308
Inch - Metric	Metric
closure type:	Open
Contact Angle	40 Degree
Cage Material	Brass
D ₁	65.55 mm
d ₂	48.08 mm
d ₁	56.25 mm

cage material:	Brass
Keyword String	Angular Contact
overall width:	18 mm
contact angle:	40 °
fillet radius:	1 mm
bore diameter:	40 mm
Bearing number	7208 BEGAY
Limiting speed	10000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Reference speed	10000 r/min
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Outside Diameter	3.15 Inch 80 Millimeter
Manufacturer URL	http://www.skf.com
Weight / Kilogram	0.37
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	80 mm
outer ring width:	18 mm
Manufacturer Name	SKF
Bore Diameter (mm)	80
r _b max.	0.6 mm
r _a max.	1 mm
D _b max.	75.8 mm
D _a max.	73 mm
d _a min.	47 mm
Number of Bearings	1 (Single)

Internal Clearance	C0-Medium
Outer Diameter (mm)	40
internal clearance:	C0
D_a - max.	73 mm
Calculation factor A	0.0109
$r_{1,2}$ min.	1.1 mm
d_a - min.	47 mm
Minimum Buy Quantity	N/A
Mounting Arrangement	Universal
$r_{3,4}$ min.	0.6 mm
r_a - max.	1 mm
r_b - max.	0.6 mm
Calculation factor X	0.57
Calculation factor e	1.14
D_b - max.	75.8 mm
d_1 ?	56.25 mm
row type & fill slot:	Single-Row Non-Fill Slot
D_1 ?	65.55 mm
d_2 ?	48.08 mm
Harmonized Tariff Code	8482.10.50.28
Calculation factor - X	0.35
Calculation factor - e	1.14
$r_{1,2}$ - min.	1.1 mm
$r_{3,4}$ - min.	0.6 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7208 BEGAY
Basic dynamic load rating C	36.4 kN
radial static load capacity:	26 kN
radial dynamic load capacity:	36.4 kN

Basic dynamic load rating - C	36.4 kN
Maximum Capacity / Filling Slot	No
Calculation factor Y_0	0.52
Calculation factor Y_2	0.93
Calculation factor Y_1	0.55
Calculation factor k_r	0.095
Fatigue load limit P_u	1.1 kN
Fatigue load limit - P_u	1.1 kN
Calculation factor - k_a	1.4
Calculation factor - k_r	0.095
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Calculation factor - Y_0	0.26
Basic static load rating C_0	26 kN
Basic static load rating - C_0	26 kN