



Bearing No. 7208 BEP

a	34 mm
d	40 mm
D	80 mm
B	18 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
Width	0.709 Inch 18 Millimeter
UNSPSC	31171531
series:	72
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	80x40x18
Inventory	0.0
Width (mm)	18
Weight / LBS	0.785
maximum rpm:	11000 RPM
Flush Ground	No
Mass bearing	0.37 kg
Contact Angle	40 Degree
Cage Material	Polymer
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d_1	56.25 mm
d_2	48.08 mm
D_1	65.55 mm

Bearing number	7208 BEP
Keyword String	Angular Contact
fillet radius:	1 mm
contact angle:	40 °
overall width:	18 mm
cage material:	Nylon
bore diameter:	40 mm
Limiting speed	10000 r/min
finish/coating:	Uncoated
Reference speed	10000 r/min
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Outside Diameter	3.15 Inch 80 Millimeter
Manufacturer URL	http://www.skf.com
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
outer ring width:	18 mm
outside diameter:	80 mm
precision rating:	Not Rated
Manufacturer Name	SKF
Weight / Kilogram	0.36
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
d _a min.	47 mm
Bore Diameter (mm)	80
D _a max.	73 mm
D _b max.	75.8 mm
r _a max.	1 mm

r_b max.	0.6 mm
Outer Diameter (mm)	40
internal clearance:	C0
$r_{1,2}$ min.	1.1 mm
Calculation factor A	0.0102
Calculation factor e	1.14
Calculation factor X	0.57
$r_{3,4}$ min.	0.6 mm
Minimum Buy Quantity	N/A
D_a - max.	73 mm
r_b - max.	0.6 mm
r_a - max.	1 mm
D_b - max.	75.8 mm
d_a - min.	47 mm
d_2 ?	48.08 mm
D_1 ?	65.55 mm
d_1 ?	56.25 mm
row type & fill slot:	Single-Row Non-Fill Slot
Calculation factor - X	0.35
Calculation factor - e	1.14
Harmonized Tariff Code	8482.10.50.28
$r_{1,2}$ - min.	1.1 mm
$r_{3,4}$ - min.	0.6 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7208 BEP
Basic dynamic load rating C	34.5 kN
radial static load capacity:	26 kN
Basic dynamic load rating - C	34.5 kN
radial dynamic load capacity:	37.7 kN

Maximum Capacity / Filling Slot	No
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor k_r	0.095
Fatigue load limit P_u	1.02 kN
Calculation factor Y_0	0.52
Fatigue load limit - P_u	1 kN
Calculation factor - Y_2	0.57
Calculation factor - Y_1	
Calculation factor - k_a	1.4
Calculation factor - Y_0	0.26
Calculation factor - k_r	0.095
Basic static load rating C_0	24 kN
Basic static load rating - C_0	24 kN