



Bearing No. 7208BDT

| | |
|--------------------|------------------|
| D | 80 mm |
| a | 16.2 mm |
| C | 18 mm |
| B | 18 mm |
| d | 40 mm |
| r1 | 0.6 mm |
| 2B | 36 mm |
| Width | 18 mm |
| r min. | 1.1 mm |
| Weight | 0.380 Kg |
| ra max. | 0.6 mm |
| r1 min. | 0.6 mm |
| da min. | 45 mm |
| Da max. | 75 mm |
| ra (max) | 1 mm |
| da1 (min) | 47 mm |
| Bore Size | 40 mm |
| Enclosure | Open |
| Bore Type | Cylindrical Bore |
| ra1 (max) | 0.6 mm |
| Size (mm) | 40x80x18 |
| da2 (min) | 45 mm |
| Da2 (max) | 75 mm |
| Da1 (max) | 73 mm |
| Width (mm) | 18 |
| Configuration | Duplex |
| Bearing number | 7208BDT |
| Angle (?) | 40 ° |
| Outside Diameter | 80 mm |
| Static Load Rating | 47,500 N |

| | |
|-------------------------------|------------|
| Bore Diameter (mm) | 40 |
| Dynamic Load Rating | 54,000 N |
| Outer Diameter (mm) | 80 |
| Limiting Speed - Oil | 7,200 rpm |
| Fillet Radius/Chamfer | 1.1 mm |
| Limiting Speed - Grease | 5,300 rpm |
| (Grease) Lubrication Speed | 5300 r/min |
| Basic dynamic load rating (C) | 54 kN |
| Basic static load rating (C0) | 47,5 kN |