



Bearing No. 7208C

a	-2.1 mm
d	40 mm
D	80 mm
B	18 mm
C	18 mm
r1	0.6 mm
a -	2,1 mm
Width	18 mm
Weight	0,38 Kg
r min.	1,1 mm
ra max.	1 mm
Da max.	73 mm
da min.	47 mm
r1 min.	0,6 mm
ra (max)	1 mm
Da1 (max)	73 mm
Da2 (max)	75 mm
da2 (min)	47 mm
da1 (min)	47 mm
Size (mm)	40x80x18
Enclosure	Open
Bore Type	Cylindrical Bore
Bore Size	40 mm
ra1 (max)	0.6 mm
Width (mm)	18
Configuration	Single Row
Bearing number	7208C
Angle (?)	15 °
Outside Diameter	80 mm
Static Load Rating	25,400 N

Bore Diameter (mm)	40
Dynamic Load Rating	36,500 N
Outer Diameter (mm)	80
Limiting Speed - Oil	18,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	13,000 rpm
(Grease) Lubrication Speed	19500 r/min
Basic static load rating (C0)	25,4 kN
Basic dynamic load rating (C)	36,5 kN