



Bearing No. KT 182519

| | |
|------------------|---|
| Bc | 19 mm |
| Ew | 25 mm |
| Fw | 18 mm |
| Bore | 0.709 Inch 18 Millimeter |
| Noun | Roller Assembly |
| Width | 0.748 Inch 19 Millimeter |
| Weight | 0,021 Kg |
| UNSPSC | 31171512 |
| Category | Needle Non Thrust Roller Bearing |
| Retainer | Yes |
| Enclosure | Not Applicable |
| Inventory | 0.0 |
| Separable | No |
| Component | Roller Assembly Only |
| Closed End | Not Applicable |
| Weight / LBS | 0.046 |
| Inch - Metric | Metric |
| Self Aligning | No |
| Product Group | B04144 |
| Bearing number | KT 182519 |
| Keyword String | Bearing Needle |
| Thrust Bearing | No |
| Other Features | C3 Clearance |
| Rolling Element | Needle Roller Bearing |
| Outside Diameter | 0.984 Inch 25 Millimeter |
| Manufacturer URL | http://www.ikont.com |
| Long Description | 18MM Bore; 25MM Outside Diameter; |

| | |
|-------------------------------|--|
| | 19MM Width; Needle Roller Bearing; Roller Assembly Only; Not Self Aligning; Retainer; Single Row of Rollers; Not Separable |
| Manufacturer Name | IKO |
| Weight / Kilogram | 0.02 |
| Bore Diameter (mm) | 18 |
| Outer Diameter (mm) | 25 |
| Minimum Buy Quantity | N/A |
| Harmonized Tariff Code | 8482.99.65.30 |
| Manufacturer Item Number | KT182519C3 |
| Number of Rows of Rollers | Single Row |
| Basic static load rating (C0) | 21,4 kN |
| Basic dynamic load rating (C) | 18,7 kN |