



Bearing No. KT 202627

|                  |   |
|------------------|---|
| Bc               | 27 mm   |
| Fw               | 20 mm   |
| Ew               | 26 mm   |
| Noun             | Roller Assembly   |
| Bore             | 0.787 Inch   20 Millimeter                              |
| Width            | 1.063 Inch   27 Millimeter                              |
| Weight           | 0,0265 Kg   |
| UNSPSC           | 31171512  |
| Category         | Needle Non Thrust Roller Bearing                        |
| Retainer         | Yes   |
| Enclosure        | Not Applicable  |
| Inventory        | 0.0   |
| Separable        | No  |
| Component        | Roller Assembly Only                                    |
| Closed End       | Not Applicable  |
| Weight / LBS     | 0.058   |
| Inch - Metric    | Metric  |
| Self Aligning    | No  |
| Product Group    | B04144  |
| Bearing number   | KT 202627   |
| Keyword String   | Bearing Needle  |
| Thrust Bearing   | No  |
| Other Features   | C3 Clearance  |
| Rolling Element  | Needle Roller Bearing                                   |
| Outside Diameter | 1.024 Inch   26 Millimeter                              |
| Manufacturer URL | <a href="http://www.ikont.com">http://www.ikont.com</a> |
| Long Description | 20MM Bore; 26MM Outside Diameter;                       |

|                               |  |
|-------------------------------|--|
|                               | 27MM Width; Needle Roller Bearing; Roller Assembly Only; Not Self Aligning; Retainer; Single Row of Rollers; Not Separable |
| Manufacturer Name             | IKO  |
| Weight / Kilogram             | 0.03   |
| Bore Diameter (mm)            | 20   |
| Outer Diameter (mm)           | 26   |
| Minimum Buy Quantity          | N/A  |
| Harmonized Tariff Code        | 8482.99.65.30  |
| Manufacturer Item Number      | KT202627C3   |
| Number of Rows of Rollers     | Single Row   |
| Basic static load rating (C0) | 37,3 kN  |
| Basic dynamic load rating (C) | 26 kN  |