



Bearing No. MFJ-1312

| | |
|---------|------------|
| D | 19 mm |
| d | 10 |
| C | 12 mm |
| B1 | 12.5 |
| B_ | 12.5 |
| da | 12 |
| C0 | 7.364 |
| ra | 0.3 |
| d1 | 10 |
| D_ | 19 |
| C1 | 1 mm |
| Fw | 13 mm |
| yobi | MFJ-1312 |
| Pmax | 3400 |
| ND-Z | 13 |
| C1_C2 | 1 |
| NC-DA | 2.273 |
| N-SDM | 15.273 |
| NB-DI | 0 |
| NC-SLR | 7.47 |
| Weight | 0,0095 Kg |
| n_yobi | FIR-101312 |
| LangID | 1 |
| mass_i | 9.5 |
| NA-DEX | 17.559 |
| N-KBRG | 8231 |
| NC-KMS | 13 |
| NC-RAC | 0 |
| OIL rpm | 26000 |
| GRS rpm | 16000 |

| | |
|-------------------------------|-------------------------|
| hidYobi | MFJ-1312 |
| NC-SLR1 | 0 |
| hidTable | ecat_NSDCNR |
| Size (mm) | 13x19x12 |
| Prod_Type3 | NRB_DC_FJ- MFJ_WC_CT |
| Width (mm) | 12 |
| Bearing number | MFJ-1312 |
| Bore Diameter (mm) | 13 |
| Outer Diameter (mm) | 19 |
| (Grease) Lubrication Speed | 16000 r/min |
| Basic dynamic load rating (C) | 6950 kN |