



Bearing No. F623ZZ

| | |
|------|---------|
| C | 0.63 |
| d | 3 mm |
| D | 10 mm |
| B | 4 mm |
| B1 | 4 |
| db | 4.3 |
| Cr | 64 |
| D_ | 10 |
| C0 | 0.218 |
| C2 | 1 |
| fo | 12.35 |
| B_ | 4 |
| rb | 0.15 |
| C1 | 1 mm |
| Z_ | 7 |
| D1 | 11,5 mm |
| D2 | 11.5 |
| r1 | 0.15 |
| DE_ | 7.528 |
| D_1 | 11.5 |
| C_1 | 1 |
| DI_ | 4.352 |
| DA_ | 1.588 |
| SRE | 0.89 |
| C0r | 22 |
| SRI | 0.89 |
| SDM_ | 5.94 |
| SRIX | 0.02 |
| SREX | 0.02 |
| SRIN | 0 |

| | |
|-------------------------------|--------------|
| KBRG | 6141 |
| mass | 1.86 |
| SREN | 0 |
| yobi | F623ZZ |
| LangID | 1 |
| Weight | 1,86 Kg |
| r min. | 0,15 mm |
| db max. | 4,3 mm |
| GRS rpm | 50000 |
| hidYobi | F623ZZ |
| rb max. | 0,15 mm |
| hidTable | ecat_NSESBMF |
| Size (mm) | 3x11.5x4 |
| Prod_Type3 | ESM_MD_WF_ZZ |
| Width (mm) | 4 |
| Bearing number | F623ZZ |
| Bore Diameter (mm) | 3 |
| Outer Diameter (mm) | 11,5 |
| Basic static load rating (C0) | 218 kN |
| Basic dynamic load rating (C) | 630 kN |