



Bearing No. 7318 BECBP

a	80 mm
d	90 mm
D	190 mm
B	43 mm
Noun	Bearing
Bore	3.543 Inch 90 Millimeter
Width	1.693 Inch 43 Millimeter
UNSPSC	31171531
series:	73
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	190x90x43
Inventory	0.0
Width (mm)	43
Weight / LBS	10.968
maximum rpm:	4500 RPM
Flush Ground	Yes
Mass bearing	5.2 kg
Contact Angle	40 Degree
Cage Material	Polymer
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d ₂	108.97 mm
d ₁	129.2 mm
D ₁	153.1 mm

Other Features	Normal Axial Internal Clearance
fillet radius:	2.5 mm
contact angle:	40 °
overall width:	43 mm
cage material:	Nylon
bore diameter:	90 mm
Keyword String	Angular Contact
Bearing number	7318 BECBP
Limiting speed	4500 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Reference speed	4500 r/min
Long Description	90MM Bore; 190MM Outside Diameter; 43MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Outside Diameter	7.48 Inch 190 Millimeter
Manufacturer URL	http://www.skf.com
Weight / Kilogram	4.98
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	190 mm
Manufacturer Name	SKF
outer ring width:	43 mm
d _a min.	104 mm
Number of Bearings	1 (Single)
Bore Diameter (mm)	190
r _b max.	1 mm
r _a max.	2.5 mm

Internal Clearance	CB
D _b max.	183 mm
D _a max.	176 mm
internal clearance:	C0
Outer Diameter (mm)	90
r _{1,2} min.	3 mm
Calculation factor A	0.333
Calculation factor e	1.14
Calculation factor X	0.57
Mounting Arrangement	Universal
r _{3,4} min.	1.1 mm
r _b - max.	1 mm
r _a - max.	2.5 mm
D _b - max.	183 mm
d _a - min.	104 mm
Minimum Buy Quantity	N/A
D _a - max.	176 mm
D ₁ ?	153.1 mm
d ₂ ?	108.97 mm
d ₁ ?	129.2 mm
row type & fill slot:	Single-Row Non-Fill Slot
Calculation factor - X	0.35
Calculation factor - e	1.14
r _{1,2} - min.	3 mm
r _{3,4} - min.	1.1 mm
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
Manufacturer Item Number	7318 BECBP
Basic dynamic load rating C	166 kN
radial static load capacity:	146 kN

radial dynamic load capacity:	166 kN
Basic dynamic load rating - C	166 kN
Maximum Capacity / Filling Slot	No
Calculation factor Y_0	0.52
Calculation factor Y_2	0.93
Calculation factor Y_1	0.55
Calculation factor k_r	0.1
Fatigue load limit P_u	5.3 kN
Calculation factor - k_r	0.1
Calculation factor - Y_0	0.26
Fatigue load limit - P_u	5.3 kN
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Calculation factor - k_a	1.6
Basic static load rating C_0	146 kN
Basic static load rating - C_0	146 kN