



Bearing No. 7318 BEGAM

a	80 mm
d	90 mm
D	190 mm
B	43 mm
Noun	Bearing
Bore	3.543 Inch 90 Millimeter
Width	1.693 Inch 43 Millimeter
UNSPSC	31171531
series:	73
Preload	Light
Category	Angular Contact Ball Bearing
Inventory	0.0
Size (mm)	190x90x43
Snap Ring	No
Enclosure	Open
Width (mm)	43
Flush Ground	Yes
Mass bearing	5.2 kg
D_1	153.1 mm
Inch - Metric	Metric
Contact Angle	40 Degree
Cage Material	Brass
d_2	108.97 mm
d_1	129.2 mm
closure type:	Open
Product Group	B00308
cage material:	Brass

Keyword String	Angular Contact
overall width:	43 mm
contact angle:	40 °
fillet radius:	2.5 mm
bore diameter:	90 mm
Bearing number	7318 BEGAM
Limiting speed	4500 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Reference speed	4500 r/min
Outside Diameter	7.48 Inch 190 Millimeter
Manufacturer URL	http://www.skf.com
Long Description	90MM Bore; 190MM Outside Diameter; 43MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Brass Cage; 40 Degree; 1 (Single);
Manufacturer Name	SKF
precision rating:	ABEC 3 (ISO Class 6)
outside diameter:	190 mm
outer ring width:	43 mm
Weight / Kilogram	5.634
Number of Bearings	1 (Single)
d _a min.	104 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	190
r _b max.	1 mm
r _a max.	2.5 mm

D_b max.	183 mm
D_a max.	176 mm
Outer Diameter (mm)	90
internal clearance:	C0
$r_{3,4}$ min.	1.1 mm
$r_{1,2}$ min.	3 mm
Calculation factor A	0.333
r_a - max.	2.5 mm
D_b - max.	183 mm
D_a - max.	176 mm
Minimum Buy Quantity	N/A
d_a - min.	104 mm
Mounting Arrangement	Universal
Calculation factor e	1.14
Calculation factor X	0.57
r_b - max.	1 mm
D_1 ?	153.1 mm
d_2 ?	108.97 mm
d_1 ?	129.2 mm
row type & fill slot:	Single-Row Non-Fill Slot
$r_{1,2}$ - min.	3 mm
$r_{3,4}$ - min.	1.1 mm
Harmonized Tariff Code	8482.10.50.28
Calculation factor - e	1.14
Calculation factor - X	0.35
Number of Rows of Balls	Single Row
Manufacturer Item Number	7318 BEGAM
Basic dynamic load rating C	166 kN
Basic dynamic load rating - C	166 kN
Maximum Capacity /	No

Filling Slot	
Fatigue load limit P_u	5.3 kN
Calculation factor k_r	0.1
Calculation factor Y_0	0.52
Calculation factor Y_2	0.93
Calculation factor Y_1	0.55
Fatigue load limit - P_u	5.3 kN
Calculation factor - Y_2	0.57
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - k_r	0.1
Calculation factor - k_a	1.6
Basic static load rating C_0	146 kN
Basic static load rating - C_0	146 kN