



### Bearing No. 7210C

|                    |          |
|--------------------|----------|
| D                  | 90 mm    |
| d                  | 50 mm    |
| B                  | 20 mm    |
| C                  | 20 mm    |
| a                  | 19.4 mm  |
| f0                 | 14.6     |
| Cu                 | 2.20     |
| Cr                 | 56.0     |
| C0r                | 34.1     |
| a(mm)              | 19.4     |
| r(min)             | 1.1      |
| Weight             | 0.485 Kg |
| r min.             | 1.1 mm   |
| r1 min.            | 0.6 mm   |
| Da max.            | 83 mm    |
| ra max.            | 1 mm     |
| da(min)            | 57       |
| r1(min)            | 0.6      |
| Da(max)            | 83       |
| ra(max)            | 1        |
| da min.            | 57 mm    |
| Oil lub.           | 12000    |
| Size (mm)          | 50x90x20 |
| Width (mm)         | 20       |
| Grease lub.        | 9600     |
| Bearing No.        | 7210C    |
| Bearing number     | 7210C    |
| Angle (?)          | 15 °     |
| (Refer.)Mass(kg)   | 0.485    |
| Bore Diameter (mm) | 50       |
|                    |          |

|                            |             |
|----------------------------|-------------|
| Outer Diameter (mm)        | 90          |
| (Oil) Lubrication Speed    | 16000 r/min |
| (Grease) Lubrication Speed | 12000 r/min |